



GLOBORX
钴铂仕

硬质合金锯齿刀片

Series of cemented carbide saw tips



GLOBORX
钴铂仕

株洲钴铂仕硬质合金有限公司



GLOBORX
钨钼钨

公司简介

株洲钨钼钨硬质合金有限公司集硬质合金产品生产、研发、销售、技术服务为一体。公司拥有当今世界先进的生产工艺技术，拥有一支强大的科研开发队伍，科研人员占员工总数的20%以上。具有世界一流的可转位数控刀片生产线及配套刀具生产线、整体硬质合金孔加工刀具生产线、机夹、焊接刀片生产线、模具成品加工生产线、地矿工具生产线，并成立了集科研、应用研究为一体的研发中心。

公司主打产品硬质合金焊接刀片、机夹刀片、数控刀片、数控刀具、圆盘铣刀、整体合金铣刀、拉丝模、冷墩模、地矿合金、锯齿片、木工刀片、硬质合金板材、硬质合金圆棒、硬质合金模具、异型合金、硬质合金粉末，以及地矿工具、深加模具、潜孔钻头、钎头、锚杆钻头、金刚石锯片、金刚石钻头、机床配套工具、电线电缆等，并代理日本三菱、东芝、京瓷、肯纳、三特等国外数控刀片及数控刀具。

公司具有近二十多年的经营历史，拥有30000多个品种产品，具有自主进出口权，产品远销世界各地，产品质量受到广大用户的一致好评。在世界各地客户中享有良好的声誉。

The company is at its disposal a world' s first class production line for index-able cemented carbide inserts and compatible tools, a production line for solid bore machining tools /solid end mills, a production for conventional inserts and a production line for ceramic inserts and their structural parts, and it has set up an R&D center that combines in one scientific research and research on applications. The company is bringing out from time to time advanced cutting tools and bore machining tools suitable for applications in industries of molds, automobiles and aviation. The company can also manufacture make various cutting tools as per drawings and samples based on the different requirements of customers and provide a whole package of solutions for mechanical machining and manufacturing.

The company has been awarded GB/T19001-ISO9001 Quality System Certificate and GB/T24001-ISO14001 Environment Management System Certificate. The corporation' s "Diamond" Brand cemented carbide was awarded the title of China' s famous brand on Sept. 1st, 2004 at the Great Hall of the People at "a commendation conference for China' s famous brands and excellent quality management" . In the market investigation and study of wide scope made by Vogel' s Beijing Consulting Company of Germany' s Vogel Industrial Media Group from May 2004 to March 2005, "Diamond" came out with talent showing itself and was honored as the nation' s tooling that is most welcome.

网址/Website: <https://globos.1688.com>

<https://www.zgloborx.com> <https://www.zomgoo.com>


电话/Tel:0731-22588953 手机/Mb:+8613873336879

邮箱: info@zgloborx.com

硬质合金锯齿牌号性能及用途推荐 The grades, properties and recommended applicant of cemented carbide saw tips

牌号 Grade	物理力学性能 Physical and mechanical properties			ISO分类 分組代号 ISO Code	推荐用途 Applications recommended	焊接建议 Proposal for welding
	密度 Density g/cm ³	硬度 Hardness HRA(HV)	抗弯强度 TRS Mpa			
YG6	14.6 - 15.0	≥90.0	≥1800	K20	适用于普通木材切割锯片 For the cutting of ordinary wood	可使用电阻焊, 温度不宜过高 use resistance welding, and the temperature should be not too high
YG8	14.6 - 14.9	≥89.5	≥1900	K30	适用于普通木材切割锯片、 亦可用于普通切铝锯片 For the cutting of ordinary wood, also for aluminum	可使用电阻焊, 温度不宜过高 use resistance welding, and the temperature should be not too high
JX20	14.4 - 14.7	≥90.0	≥2000	K20	适用于普通木材切割锯片 For the cutting of ordinary wood	可使用电阻焊, 温度不宜过高 use resistance welding, and the temperature should be not too high
JX25	14.3 - 14.6	≥89.5	≥2100	K30	适用于普通木材切割锯片、 亦可用于普通切铝锯片 For the cutting of ordinary wood, also for aluminum	可使用电阻焊, 温度不宜过高 use resistance welding, and the temperature should be not too high
JX5	14.6 -15.0	≥90.5	≥1900	K10	适用于硬木材、回收木料及 铝合金切割锯片 Applies to the cutting of hard wood, recycling wood and aluminum	可使用电阻焊, 温度不宜过高 use resistance welding, and the temperature should be not too high
JX9	14.5 -14.9	≥90.5	≥2000	K10	适用于铝合金及铜、铅等 有色金属专业切割锯片 Applies to the cutting of aluminum opper and lead, non-ferrous	建议使用高频焊接 recommend the high-frequency welding
YG6X	14.7 -15.0	≥91.5	≥1800	K10	适用于木材的专业切割锯片 Applies to the cutting of the timber	建议使用高频焊接 recommend the high-frequency welding
JX10	14.6 -15.1	≥93.3	≥2500	K05	适用于硬木材的专业切割锯片, 亦可用于软金属切割锯片 Applies to the cutting of hard Wood, also can be used for The cutting of soft metal	建议使用高频焊接 recommend the high-frequency welding
JX15	14.6 -15.0	≥92.5	≥2400	K05	适用于硬木材及铝合金的切割锯片 Applies to the cutting of hard wood and aluminum	建议使用高频焊接 recommend the high-frequency welding
JX35	14.9 -15.2	≥93.5	≥2000	K01	适用于工业胶合板、密度板及夹层板等专业切割锯片 Apply to the cutting of plywood, mdf board and sandwich board	建议使用高频焊接 recommend the high-frequency welding
JX40	12.8 -13.2	≥90.5	≥2000	P40	适用于钢材的专业切割用锯片 Apply to the cutting of steel	建议使用高频焊接 recommend the high-frequency welding

常规锯齿刀片标准代号尺寸对照表



型号 type	基本尺寸 Dimension (mm)					
	L	B	C	α°	β°	R
Jx4215	4.2	1.5	2.7	30	20	0.5
JX4514	4.5	1.4	3.0	28	15	0.6
JX4515	4.5	1.5	3.5	30	27	0.5
JX4615	4.6	1.5	3.6	30	26.6	0.5
JX4713	4.7	1.3	3.4	33	-	0.5
JX4715	4.7	1.5	3.7	30	30	0.5
JX4816	4.8	1.6	3.5	30	17	0.5
JX5014	5.0	1.4	3.5	30	15	0.5
JX5014A	5.0	1.4	3.5	20	15	0.5
JX5015	5.0	1.5	3.5	20	20	0.5
JX5015A	5.0	1.5	4.0	30	26.5	0.5
JX5015B	5.0	1.5	4.5	20	45	-
JX5015C	5.0	1.5	3.6	30	$0.5 \times 45^{\circ}$	$0.5 \times 45^{\circ}$
JX5016	5.0	1.6	4.0	30	22	0.5
JX5016A	5.03	1.63	4.3	25	$0.7 \times 45^{\circ}$	0.6
JX5016B	5.0	1.6	3.4	20	20°	0.5
JX5017	5.0	1.7	3.7	20	17.1	0.2
JX5022	5.0	2.2	2.5	30	15	0.5
JX5025	5.0	2.5	3.5	25	45	0.2
Jx5115	5.1	1.5	3.8	28	$0.5 \times 45^{\circ}$	0.2
JX5116	5.1	1.6	4.0	30	22	0.5
JX5216	5.2	1.6	3.5	25	20	0.5
JX5218	5.2	1.8	3.8	18	40	0.5
JX5220	5.2	2.0	2.7	30	15	0.5
JX5315	5.3	1.5	3.8	20	20	0.5
JX53155	5.3	1.55	4.3	28	15	0.5
JX5315A	5.3	1.5	4.0	30	20	0.5

* 我公司可以根据客户提供的图纸和样品制作模具, 生产各种其它形状及尺寸的锯齿产品。

We can produce moulds as per your drawings and samples to the production of saw tips with different shapes and sizes.

常规锯齿刀片标准代号尺寸对照表

型号 type	基本尺寸 Dimension (mm)					
	L	B	C	α°	β°	R
JX5316	5.3	1.6	4.0	30	20	0.5
JX5317	5.3	1.7	4.1	10	18	0.5
JX5417	5.4	1.7	4.1	20	20	0.5
JX5515	5.5	1.5	3.9	10	17	0.5
JX55155	5.5	1.55	4.3	28	15	0.5
JX5515A	5.5	1.5	4.3	28	-	0.5
JX5515B	5.5	1.5	5.0	30	0.48 x 45°	0.8
JX5516	5.5	1.6	4.3	28	15	0.5
JX5516A	5.5	1.6	3.9	30	14	0.5
JX5516B	5.5	1.6	3.9	20	14	0.5
JX5516C	5.5	1.6	4.3	28	15	0.5
JX5517	5.5	1.7	3.7	15	20	0.5
JX5517A	5.5	1.7	4.2	30	20	0.5
JX5517B	5.5	1.7	3.7	30	21	0.5
JX5517C	5.5	1.7	3.7	25	21.2	0.5
JX5518	5.5	1.8	3.7	30	24	0.5
JX5518A	5.5	1.8	3.9	25	25	0.5
JX5616B	5.6	1.6	4.3	30	0.5 x 45°	
JX5618	5.6	1.8	3.3	24	-	0.5
JX5716	5.7	1.6	4.3	30	20	0.5
JX5717	5.7	1.7	4.3	30	20	0.5
JX5717A	5.7	1.7	4.3	25	70	0.5
JX5717B	5.7	1.7	4.3	30	20	0.5
JX5717C	5.7	1.7	4.3	30	20	0.5
JX5719	5.7	1.9	4.4	25	25	0.5
JX5815	5.8	1.5	4.6	30	14	0.5
Jx5818	5.8	1.8	3.0	30	15	0.5
Jx5820	5.8	2.0	4.6	23	26	0.3
Jx5916	5.9	1.6	4.4	30	17	0.5
Jx6015	6.0	1.5	4.8	28	15	0.5
JX6016	6.0	1.6	4.6	30	20	0.5
JX6017	6.0	1.7	4.6	30	20	0.5
JX6018	6.0	1.8	4.5	20	20	0.5
JX6018A	6.0	1.8	4.6	30	20	0.5
JX6018B	6.0	1.8	4.4	30	20	0.5

★ 我公司可以根据客户提供的图纸和样品制作模具, 生产各种其它形状及尺寸的锯齿产品。

We can produce moulds as per your drawings and samples to the production of saw tips with different shapes and sizes.

常规锯齿刀片标准代号尺寸对照表

型号 type	基本尺寸 Dimension (mm)					
	L	B	C	α°	β°	R
JX6520F	6.5	2.0	4.4	25	20	0.5
JX6522	6.5	2.2	4.9	30	29	0.5
JX6523	6.5	2.3	4.6	20	20	0.5
JX6523A	6.5	2.3	4.1	45	30	0.9
JX6524	6.5	2.4	5.9	22	30	0.5×45°
JX6524A	6.5	2.4	4.3	30	27	0.5
JX6525	6.5	2.5	4.3	25	20	0.5
JX6530	6.5	3.0	4.4	20	32	0.2
JX6720	6.7	2.0	5.1	30	20	0.5
JX6817	6.8	1.7	4.6	25	17.6	0.2×45°
JX6820	6.8	2.0	4.8	20	15	0.5
JX6822	6.8	2.2	4.6	25	28.6	0.2×45°
JX7020	7.0	2.0	5.4	20	20	0.5
JX7020A	7.0	2.0	6.5	28	0.48×45°	1.0
JX7020B	7.0	2.0	5.4	30	20	0.5
JX7022	7.0	2.2	5.5	25	30	0.5
JX7022A	7.0	2.2	5.5	30	20	0.5
JX7022F	7.0	2.2	5.0	12	21	0.5
JX7023	7.0	2.3	5.1	30	30	0.5
JX7025	7.0	2.45	4.8	14	28	0.3
JX7025B	7.0	2.5	4.0	5	22	0.4
JX7030	7.0	3.0	4.1	30	30	0.5
JX7123	7.1	2.3	4.9	25	30° 58'	0.2×45°
JX7221	7.2	2.1	5.1	13	23	0.5
JX7223	7.2	2.3	4.5	25	30	0.5
JX7418	7.4	1.8	5.1	22	20	0.5
JX7517	7.5	1.7	5.0	20	25	0.5
JX7519	7.5	1.9	5.2	30	21	0.5
JX7520	7.5	2.0	6.7	28	45	1.0
JX7520A	7.5	2.0	5.2	30	17	0.5
JX7522	7.5	2.5	5.0	30	20	0.5
JX7523	7.5	2.3	5.0	27	19	0.3
JX7524	7.5	2.4	5.8	22	30	0.5×45°
JX7524A	7.5	2.0	5.0	30	24	-
Jx7525	7.5	2.5	5.3	30	30	0.5

★ 我们公司可以根据客户提供的图纸和样品制作模具,生产各种其它形状及尺寸的锯齿产品。
We can produce moulds as per your drawings and samples to the production of saw tips with different shapes and sizes.

常规锯齿刀片标准代号尺寸对照表

型号 type	基本尺寸 Dimension (mm)					
	L	B	C	α°	β°	R
JX7525A	7.5	2.5	5.3	30	30	0.5
JX7525E	7.5	2.5	5.0	12	20	0.5
JX7821	7.8	2.1	5.5	27	14	0.5
JX7828	7.8	2.8	5.2	25	20	0.5
JX7926	7.9	2.6	6.0	30	20	0.5
JX8020	8.0	2.0	5.5	27	13	0.5
JX8021	8.0	2.1	6.0	30	20	0.5
JX8022	8.0	2.2	5.8	25°	17° 39'	0.2
JX8023	8.0	2.3	5.3	28	20	0.5
JX8023A	8.0	2.3	6.6	28	34	1.0
JX8023B	8.0	2.3	5.8	25	1.5×45°	0.2
JX8023F	8.0	2.3	5.0	25	20	0.5
JX8024	8.0	2.4	5.7	12	23	0.5
JX8024A	8.0	2.4	5.6	25	25	0.5
JX8024B	7.92	2.36	6.0	30	30	0.6
JX8024C	8.0	2.4	5.4	20	19	0.5
JX8024D	8.0	2.4	5.4	30	20	0.5
JX8024E	8.0	2.4	6.9	40	20	0.5
JX8025	8.0	2.5	4.0	28	15	0.75
JX8025A	8.0	2.5	5.5	25	31	0.2×45°
JX8025B	8.0	2.5	5.4	20	20	0.5
JX8027	8.0	2.7	5.5	25	20	0.5
JX8030	8.0	3.0	6.8	25	45	1.0
JX8030B	8.0	3.0	5.1	25	30	0.6
JX8120	8.1	2.0	5.5	25	21° 03'	0.2×45°
JX8223	8.2	2.3	5.7	29	22	0.5
JX8224	8.2	2.4	5.5	25	20	0.5
JX8225	8.2	2.5	5.5	25	25	0.5
JX8228	8.2	2.8	5.8	25	28	0.5
JX8228A	8.2	2.8	5.6	25	25	0.5
JX8424	8.4	2.4	6.8	30	30	0.5×45°
JX8520	8.5	2.0	6	30	16	-
JX8523	8.5	2.3	5.7	25	20	0.5
JX8524	8.5	2.4	5.5	30	20	0.5
Jx8525	8.5	2.5	5.9	30	23	0.5

★ 我公司可以根据客户提供的图纸和样品制作模具,生产各种其它形状及尺寸的锯齿产品。

We can produce moulds as per your drawings and samples to the production of saw tips with different shapes and sizes.

常规锯齿刀片标准代号尺寸对照表

型号 type	基本尺寸 Dimension (mm)					
	L	B	C	α°	β°	R
JX8525	8.5	2.5	6.5	30	20	0.5
JX8525B	8.5	2.5	6.34	60	25	0.6
JX8528	8.5	2.8	6	27	13	0.2×45°
JX8528A	8.5	2.8	6	20	20	0.5
JX8529	8.5	2.9	6	27	27	0.2×45°
JX8530	8.5	3.0	6	27	27	1.0
JX8531	8.5	3.1	6	27	27	0.2×45°
JX8533	8.5	3.3	6	27	13	0.2×45°
JX8724	8.7	2.4	5.8	25	20	0.5
JX8732	8.74	3.2	6	30	30	0.6
JX8826	8.8	2.6	6.0	25	25	0.5
JX8830	8.8	3.0	5.8	9	20	0.5
JX9023	9.0	2.3	5.3	28	20	0.5
JX9024	9.0	2.4	6	28	30	0.5
JX9025	9.0	2.5	8.5	28	57	1.0
JX9025A	9.0	2.5	5.3	28	20	0.5
JX9026	9.0	2.6	7.1	30	30	0.5×45°
JX9026A	9.0	2.6	6.0	30	20	0.5
JX9028A	9.0	2.8	7.6	20	30	0.5
JX9040	9.0	4.0	3	30	15	0.5
JX9124	9.1	2.4	6.2	25	25.8	0.2×45°
JX9125	9.1	2.5	6.5	25	20	0.5
JX9325	9.3	2.5	6.5	22	25	1.0
JX9525	9.5	2.5	6.7	20	25	0.2
JX9525C	9.5	2.5	9	28	45	1.0
JX9526	9.5	2.6	6.7	20	25	0.2×45°
JX9528	9.5	2.8	7	30	25	0.8
JX9530	9.5	3.0	6.3	25	20	0.5
JX9622	9.6	2.2	6.6	30	20	0.5
JX9632	9.6	3.2	6.8	30	30	-
JX10832	10.8	3.2	7.2	25	20	0.5
JX10028	10.0	2.8	5.0	28	16	0.75
JX10028A	10.0	2.8	7.5	27	26	0.5
JX10030	10.0	3.0	6.3	15	18	0.5
Jx10040	10.0	4.0	8.0	30	46	0.6×45°

★我可以根据客户提供的图纸和样品制作模具,生产各种其它形状及尺寸的锯齿产品。

We can produce moulds as per your drawings and samples to the production of saw tips with different shapes and sizes.


常规锯齿刀片标准代号尺寸对照表

型号 type	基本尺寸 Dimension (mm)					
	L	B	C	α°	β°	R
JX10525	10.5	2.5	10.0	28	45	1.0
JX10525A	10.5	2.5	7.0	30°	17°	0.5
JX10527A	10.5	2.7	7.2	30	20	0.5 × 45°
JX10527B	10.5	2.7	6.5	30	20	0.5
JX10527C	10.5	2.7	4.7	21	15	0.5 × 45°
JX10530	10.5	3.0	7.4	30	30	0.5
JX10540	10.5	4.0	9.3	30	30	0.7
JX10625	10.6	2.5	7.2	25	23	0.2 × 45°
JX10832	10.8	3.2	7.2	25	20	0.5
JX11027	11.0	2.7	7.8	15	20	0.3
JX11528	11.5	2.8	8.0	27	22	0.2
JX11531	11.5	3.1	8.4	27	26	0.5
JX12035	12.0	3.5	7.0	30	21	0.5
JX12042	12.0	4.2	8.0	20	10	1.0
JX12530	12.5	3.0	8.0	30	25	0.5
Jx12535	12.5	3.5	8.5	25	25	0.5

★ 我公司可以根据客户提供的图纸和样品制作模具, 生产各种其它形状及尺寸的锯齿产品。

We can produce moulds as per your drawings and samples to the production of saw tips with different shapes and sizes.

常规锯齿刀片标准代号尺寸对照表



型号 type	基本尺寸 Dimension (mm)								
	L	B	C	E	R1	R2	α°	β°	γ°
JX6525B	6.5	2.4	2.5	1.26	0	0.5	0	50	64
J99054A	6.5	2.2	1.8	1.06	0.1	0.65	0	60	40
J99053	6.5	2.2	2.03	1.06	0.15	1.015	0	60	50
J9545H	9.5	2.65	4.5	3.3	0.2	2.25	0	45	63
J01071R	6.5	2.25	2.3	1.4	0.1	0.9	10	60	45
J01071L	6.5	2.25	2.3	0.9	0.1	0.9	10	45	60

★ 我公司可以根据客户提供的图纸和样品制作模具,生产各种其它形状及尺寸的锯齿产品。


We can produce moulds as per your drawings and samples to the production of saw tips with different shapes and sizes.

锯齿刀片的主要尺寸允许公差范围

基本尺寸 Dimension (mm)							
长度L (mm)	允许公差	厚度C (mm)	允许公差	宽度B (mm)	允许公差	角度	平行度
0~5.0	+0.15 -0.15	0~2.0	+0.10 -0.05	0~2.0	+0.10 -0.05	$\pm 2^\circ$	$\leq 0.1\text{mm}$
>5.0~7.0	+0.20 -0.05			2.0~3.5	+0.15 -0.05		
>7.0~9.0	+0.20 -0.05	>2.0	+0.15 -0.05	3.5~5.0	+0.20 -0.05		
>9.0	+0.30 -0.05			>5.0	+0.25 -0.05		


★ 若客户有特殊要求,公差范围可适当调整。

The tolerances can be adjusted appropriately, if the customer has special requirements.




mm

型号 Type	尺寸 Dimensions						
	L	T	W	T1	R	α°	β°
GC5020-W	4.5	2.0	W	1.0	0.6	35	42
GC5520-W	5.0	2.0	W	1.0	0.6	35	42
GC5720-W	5.7	2.0	W	1.0	1.0	40	40
GC6022-W	6.0	2.2	W	1.09	0.7	30	40
GC6520-W	6.5	2.0	W	0.8	1.0	31	46
GC6525-W	6.5	2.5	W	1.0	0.6	36	45
GC6725-W	6.7	2.5	W	1.25	0.6	35	45
GC7022-W	7.0	2.2	W	1.1	1.1	44	44
GC7525-W	7.5	2.5	W	1.25	1.1	40	40
GC8025-W	8.0	2.5	W	1.25	1.1	35	42
GC8525-W	8.5	2.5	W	1.25	0.6	31	46
GC9025-W	9.0	2.5	W	1.25	0.6	35	45
GC9530-W	9.5	3.0	W	1.50	1.1	35	42
GC10030-W	10.0	3.0	W	1.50	1.1	35	42
GC10530-W	10.5	3.0	W	1.50	1.1	35	42




mm

型号 Type	尺寸 Dimensions					
	L	T	W	T1	α°	β°
45752	4.5	1.5	W	0.7	28	45
28601	5.0	1.5	W	1.0	28	45
25720	5.5	1.5	W	1.0	30	45
25375	6.0	1.8	W	1.2	28	45
25374	6.0	2.0	W	1.4	28	45
25376	6.5	2.0	W	1.4	28	45
25377	7.0	2.0	W	1.2	28	45
29984	7.0	2.2	W	1.8	28	70
7601	7.5	2.0	W	1.2	28	45
34471	8.0	2.3	W	1.5	28	56
9222	8.5	2.5	W	1.25	28	45
47784	8.5	3.5	W	2.0	25	65
24466	9.0	2.5	W	1.46	20	57
24467	10.0	2.5	W	1.6	20	67
31591	10.0	3.0	W	1.6	15	72
9218	10.5	2.5	W	1.3	28	45
7961	10.5	3.0	W	1.7	30	50
18276	10.5	3.5	W	2.4	28	45
19975	12.0	3.5	W	2.4	30	45
24150	12.5	4.0	W	2.7	30	70
18246	13.0	5.0	W	3.3	35	45
9201	13.5	4.0	W	2.7	25	0




mm

型号 Type	尺寸 Dimensions		
	L	W	T
WDC7125~WDC7312	7.92(0.312)	3.18~7.92(0.125~0.312)	2.36(0.093)
WEC7150~WEC7375	9.53(0.375)	3.81~9.53(0.150~0.375)	2.36(0.093)
WFC7410~WFC7687	12.70(0.500)	3.56~17.45(0.140~0.687)	3.18(0.125)
WGC7150~WGC7312	9.53(0.375)	3.81~7.92(0.150~0.312)	3.18(0.125)
WHC7110~WHC7300	8.74(0.344)	2.79~7.62(0.110~0.300)	3.18(0.125)




mm

型号 Type	尺寸 Dimensions		
	L	W	T
WA7065~WA7215	6.35(0.250)	1.65~5.46(0.065~0.215)	1.57(0.062)
WB7085~WB7312	7.14(0.281)	2.16~7.92(0.085~0.312)	1.98(0.078)
WC7100~WC7250	7.14(0.281)	2.54~6.35(0.100~0.250)	2.36(0.093)
WD7100~WD7312	7.92(0.312)	2.54~7.92(0.100~0.312)	2.36(0.093)
WE7150~WE7375	9.53(0.375)	3.81~9.53(0.150~0.375)	2.36(0.093)
WF7150~WF7750	12.70(0.500)	3.81~9.53(0.150~0.375)	3.18(0.125)
WG7150~WG7750	9.53(0.375)	3.81~19.05(0.150~0.750)	3.18(0.125)
WH7125~WH7300	8.74(0.344)	3.18~7.62(0.125~0.300)	3.18(0.125)
WQ7170~WQ7375	9.53(0.375)	4.32~9.53(0.170~0.375)	3.96(0.156)




mm

型号 Type	尺寸 Dimensions		
	L	W	T
WDC7125-WDC7312	7.92(0.312)	3.18~7.92(0.125~0.312)	2.36(0.093)
WEC7150-WEC7375	9.53(0.375)	3.81~9.53(0.150~0.375)	2.36(0.093)
WFC7410-WFC7687	12.70(0.500)	3.56~17.45(0.140~0.687)	3.18(0.125)
WGC7150-WGC7312	9.53(0.375)	3.81~7.92(0.150~0.312)	3.18(0.125)
WHC7110-WHC7300	8.74(0.344)	2.79~7.62(0.110~0.300)	3.18(0.125)



mm

型号 Type	尺寸 Dimensions		
	L	W	T
WA7065-WA7215	6.35(0.250)	1.65~5.46(0.065~0.215)	1.57(0.062)
WB7085-WB7312	7.14(0.281)	2.16~7.92(0.085~0.312)	1.98(0.078)
WC7100-WC7250	7.14(0.281)	2.54~6.35(0.100~0.250)	2.36(0.093)
WD7100-WD7312	7.92(0.312)	2.54~7.92(0.100~0.312)	2.36(0.093)
WE7150-WE7375	9.53(0.375)	3.81~9.53(0.150~0.375)	2.36(0.093)
WF7150-WF7750	12.70(0.500)	3.81~9.53(0.150~0.375)	3.18(0.125)
WG7150-WG7750	9.53(0.375)	3.81~19.05(0.150~0.750)	3.18(0.125)
WH7125-WH7300	8.74(0.344)	3.18~7.62(0.125~0.300)	3.18(0.125)
WQ7170-WQ7375	9.53(0.375)	4.32~9.53(0.170~0.375)	3.96(0.156)



mm

型号Type	尺寸Dimensions		
	L	W	T
WA8065-WA8215	6.35(0.250)	1.65-5.46(0.065-0.215)	1.57(0.062)
WB8085-WB8312	7.14(0.281)	2.16-7.92(0.085-0.312)	1.98(0.078)
WC8100-WC8250	7.14(0.281)	2.54-6.35(0.100-0.250)	2.36(0.093)
WD8100-WD8312	7.92(0.312)	2.54-7.92(0.100-0.312)	2.36(0.093)
WE8150-WE8375	9.53(0.375)	3.81-9.53(0.150-0.375)	2.36(0.093)
WF8150-WF8750	12.70(0.500)	3.81-9.53(0.150-0.375)	3.18(0.125)
WG8150-WG8750	9.53(0.375)	3.81-19.05(0.150-0.750)	3.18(0.125)
WH8125-WH8300	8.74(0.344)	3.18-7.62(0.125-0.300)	3.18(0.125)
WQ8170-WQ8375	9.53(0.375)	4.32-9.53(0.170-0.375)	3.96(0.156)

硬质合金锯齿片系列

eries of cemented carbide saw tips

